DOOR WORKS COMPANY QUOTE REQUEST FORM

Date:

Dealer: Contact: Email:	Phone #: Fax # Job Name:	Anticipated Delivery Schedule:	**Bid due by**

Door Design:

Style:
Sticking:
Panel Profile:

Other:

LEED

- ☐ MR 4.1 and 4.2 - Recycled Content
- ☐ MR 5.1 Local and Regional
- ☐ MR 5.2 Local and Regional
- ☐ IEQ 4.4 - No Added Urea-Formaldehyde

Louvers:

☐ Cutout Only ☐ Metal ☐ False ☐ True

Slat size:

Light Openings:

☐ Cutout Only ☐ SDL ☐ TDL ☐ Fire Rated (SDL)

Size:

Glass type and thickness:

Frame Requirements:

☐ Primed ☐ Un-Primed ☐ Rating:

☐ 3/4" Poplar ☐ 5/4" Poplar ☐ Hollow Metal Frame

Other:

Fire Rating: ☐ Neutral Pressure ☐ Positive Pressure

☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min

☐ Flush ☐ Match non-rated

Machining Requirements:

Factory Finishing: ☐ Prime ☐ Standard White Paint ☐ Custom Paint

Door Quantity	Pair Match	Rating	Size (in inches) Width x Length	Thick	Lite/Louver (visible lite)	Hinges	Hardware										Blocking			Special Notes & Instructions
							Cyl	Lever	Mortise	Card	Exit	Peep	T-strike	Flush bolts	Ball Catch	Other	Top	Bottom	Lock	

Other Information: